



	PANIGALE V2	PANIGALE V2 BAYLISS 1ST CHAMPIONSHIP 20TH ANNIVERSARY
ENGINE		
TYPE	Superquadro: L-twin cylinder, 4 valve per cylinder, Desmodromic, liquid cooled	Superquadro: L-twin cylinder, 4 valve per cylinder, Desmodromic, liquid cooled
DISPLACEMENT	955 cc	955 cc
BORE x STROKE	100 x 60,8 mm	100 x 60,8 mm
COMPRESSION RATIO	12.5:1	12.5:1
POWER	114 kW (155 hp) @ 10.750 rpm	114 kW (155 hp) @ 10.750 rpm
TORQUE	104 Nm (76,7 lb-ft) @ 9.000 rpm	104 Nm (76,7 lb-ft) @ 9.000 rpm
FUEL INJECTION	Electronic fuel injection system. Twin injectors per cylinder. Full ride-by-wire elliptical throttle bodies	Electronic fuel injection system. Twin injectors per cylinder. Full ride-by-wire elliptical throttle bodies
EXHAUST	2-1-2-1 system, with 2 catalytic converters and 2 lambda probes	2-1-2-1 system, with 2 catalytic converters and 2 lambda probes
TRANSMISSION		
GEARBOX	6 speed with Ducati Quick Shift (DQS) up/down EVO 2	6 speed with Ducati Quick Shift (DQS) up/down EVO 2
PRIMARY DRIVE	Straight cut gears; Ratio 1.77:1	Straight cut gears; Ratio 1.77:1
RATIO	1=37/15 2=30/16 3=27/18 4=25/20 5=24/22 6=23/24	1=37/15 2=30/16 3=27/18 4=25/20 5=24/22 6=23/24
FINAL DRIVE	Chain; Front sprocket 15; Rear sprocket 43	Chain; Front sprocket 15; Rear sprocket 43
CLUTCH	Hydraulically controlled slipper and self-servo wet multiplate clutch	Hydraulically controlled slipper and self-servo wet multiplate clutch. Self bleeding master cylinder
CHASSIS		
FRAME	Monocoque Aluminium	Monocoque Aluminium
FRONT SUSPENSION	Fully adjustable Showa BPF fork. 43 mm chromed inner tubes	Öhlins NIX30 43mm with TiN treatment, fully adjustable usd fork
FRONT WHEEL	5-spokes light alloy 3.50" x 17"	5-spokes light alloy 3.50" x 17"
FRONT TYRE	Pirelli Diablo Rosso Corsa II 120/70 ZR17	Pirelli Diablo Rosso Corsa II 120/70 ZR17
REAR SUSPENSION	Fully adjustable Sachs unit. Aluminium single-sided swingarm	Fully adjustable Öhlins TT36 monoshock. Aluminium single-sided swingarm
REAR WHEEL	5-spokes light alloy 5.50" x 17"	5-spokes light alloy 5.50" x 17"
REAR TYRE	Pirelli Diablo Rosso Corsa II 180/60 ZR17	Pirelli Diablo Rosso Corsa II 180/60 ZR17
WHEEL TRAVEL (FRONT/REAR)	120 mm (4.72 in) - 130 mm (5.12 in)	120 mm (4.72 in) - 130 mm (5.12 in)
FRONT BRAKE	2 x 320 mm semi-floating discs, radially mounted Brembo Monobloc M4.32 4-piston callipers with Bosch Cornering ABS EVO	2 x 320 mm semi-floating discs, radially mounted Brembo Monobloc M4.32 4-piston callipers with Bosch Cornering ABS EVO. Self bleeding master cylinder
REAR BRAKE	245 mm disc, 2-piston calliper with Bosch Cornering ABS EVO	245 mm disc, 2-piston calliper with Bosch Cornering ABS EVO
INSTRUMENTATION	Digital unit with 4,3" TFT colour display	Digital unit with 4,3" TFT colour display
DIMENSIONS AND WEIGHTS		
DRY WEIGHT	176 kg (388 lb)	174,5 kg (385 lb)
KERB WEIGHT*	200 kg (441 lb)	197 kg (434 lb)
SEAT HEIGHT	840 mm (33.1 in)	835 mm (32.9 in)
WHEELBASE	1.436 mm (56,5 in)	1.438 mm (56,6 in)
RAKE	24°	24°
TRAIL	94 mm (3.70 in)	99 mm (3.90 in)
FUEL TANK CAPACITY	17 l - 4.5 gallon (US)	17 l - 4.5 gallon (US)
NUMBER OF SEATS	Dual seat	Dual seat
EQUIPMENT		
SAFETY EQUIPMENT	Riding Modes, Power Modes, Bosch Cornering ABS EVO, Ducati Traction Control (DTC) EVO 2, Ducati Wheelie Control (DWC) EVO, Engine Brake Control (EBC) EVO, Auto tyre calibration	Riding Modes, Power Modes, Bosch Cornering ABS EVO, Ducati Traction Control (DTC) EVO 2, Ducati Wheelie Control (DWC) EVO, Engine Brake Control (EBC) EVO, Auto tyre calibration
STANDARD EQUIPMENT	Ducati Quick Shift (DQS) up/down EVO 2, Full LED lighting with Daytime Running Light (DRL), Sachs steering damper, Auto-off indicators	Ducati Quick Shift (DQS) up/down EVO 2, Full LED lighting with Daytime Running Light (DRL), Öhlins steering damper, Auto-off indicators, Lithium-ion battery, Silencer outlet cover in carbon fibre and titanium
ADDITIONAL EQUIPMENT		Passenger seat and footpegs kit
READY FOR	Ducati Data Analyser+ (DDA+) with GPS module, Ducati Multimedia System (DMS) and anti-theft	Ducati Data Analyser+ (DDA+) with GPS module, Ducati Multimedia System (DMS) and anti-theft
WARRANTY AND MAINTENANCE		
WARRANTY	24 months unlimited mileage	24 months unlimited mileage
MAINTENANCE SERVICE INTERVALS	12.000 km (7.500 mi) / 12 months	12.000 km (7.500 mi) / 12 months
DESMOSERVICE	24.000 km (15.000 mi)	24.000 km (15.000 mi)
EMISSIONS AND CONSUMPTION (Only for countries where Euro 5 standard applies)		
STANDARD	Euro 5	Euro 5
CO2 EMISSIONS	139 g/km	139 g/km
CONSUMPTION	6 l/100km	6 l/100km